



TYPICAL APPLICATION CHARACTERISTICS

| | |
|---|--|
| DRYING (at 20°C and 65% R.H.) | dust free: 40 – 60 minutes for re-coating: 8-10 |
| EFFECTIVE COVERAGE | >14 m ² /L depending on wood absorption |
| DILUTION (V/V) | Ready to use |
| TOOLS | Rag/brush |

APPLICATION SYSTEM

SUBSTRATES: timber already treated with finishes and wood stains.

SUBSTRATE PREPARATION: substrates must be sound, dry and with no flaking or peeling sections. The substrates to coat must be suitably cleaned to remove traces of dirt, dust, smog, etc. which could affect the treatment.

| | | |
|--|---|----------------------|
| | WOOD WITH OLD FINISHES / WOOD STAINS | |
| | BIOTONO | 1-2 COATS |

TECHNICAL SPECIFICATIONS (for contracts and quotations)

| | |
|--------------------------------|---|
| GENERAL CHARACTERISTICS | water-based revitaliser for treated wood, based on acrylic resins in water emulsion |
| DRY RESIDUE | 17 ± 1% |
| SPECIFIC WEIGHT | 1.02 ± 0.01 g/cm ³ at 20°C |



GENERAL INFORMATION AND NOTICES

Mix carefully before and during use.

Do not apply on two-component varnishes, high gloss finishes and deteriorated and greying wood. In temperature and relative humidity conditions other than those indicated, drying times may vary; at low temperatures, the re-coating time must be extended to allow the water in the first coat to evaporate completely.

Store the product in a cool place. Do not allow to freeze.

The technical information provided above is the result of careful laboratory testing and practical experience. Nevertheless, as the product is often used outside our control, we are unable to guarantee the quality of the end result. This information is subject to review by the Company.

Please carefully read the "GENERAL RECOMMENDATIONS".

CQ Rev. 1 - June 2014

"In accordance with European Directive 2004/42/EC, the VOC values displayed on the packaging refer to the dilutions and thinners specified and to tinted products based on the formulations indicated by Boero Bartolomeo SpA."