



Extra matt washable water-based paint for interiors.

This product, which has excellent filling and masking power and good hiding power, can also be used to re-coat wallpaper.

The use of special raw materials gives the product excellent brushability and an extra matt finish, masking small surface imperfections or application blemishes.

Can be used in any environment (bedrooms, living rooms, kitchens, bathrooms, etc.).

TYPICAL CHEMICAL AND PHYSICAL CHARACTERISTICS

APPEARANCE	matt	
COMPOSITION	synthetic binders in emulsion	
SPECIFIC WEIGHT	1.60 ± 0.05 g/cm ³ at 20°C	
BROOKFIELD VISCOSITY	18,000 ± 2,000 cP	G6V10 at 20°C
DRY RESIDUE	64.7 ± 0.5 % p/p	
WASHING RESISTANCE	Excellent > 5,000 Gardner cycles	UNI 10795 UNI 10560
PERMEABILITY TO WATER VAPOUR	high	UNI 10795 UNI EN ISO 7783-2
ALKALI RESISTANCE	alkali resistant	UNI 10795
DIRT PICK-UP	average	UNI 10792

For reference standards, see “Key – technical data sheets”

COLOURS

White,





TYPICAL APPLICATION CHARACTERISTICS

DRYING (at 20°C and 65% R.H.)	for recoating: 6 hours
EFFECTIVE COVERAGE	10-12 m ² /L per coat depending on substrate absorption
DILUTION (V/V)	brush: 1st coat 30%, 2nd coat 25% drinking water roller: 20-25% 1st and 2nd coat with drinking water
TOOLS	brush, roller

¹ Tints derived from bases other than BC require less dilution, up to a maximum of 5-10% by volume.

APPLICATION SYSTEM

SUBSTRATES: civil plaster, plasterboard, fibre cement, skim coated walls, suitably prepared wallpaper.

SUBSTRATE PREPARATION: substrates must be sound, dry, clean, firm and free of damp patches and traces of dirt and grease, etc. Remove flaking or chalky old paintwork by brushing or sanding. Imperfections, cracks and flaking must be removed and filled with BOEROSTUCCO.

	NEW SUBSTRATES		SUBSTRATES WITH OLD WATER-BASED PAINT RESIDUES (slightly chalky)		SUBSTRATES WITH OLD WATER-BASED PAINT RESIDUES (well-anchored washable paint)	
PRIMER	IDROACRIL or Fondo 2000	1 COAT	IDROACRIL or Fondo 2000	1 COAT	-	
FINISH	BoerOpako	2 COATS	BoerOpako	2 COATS	BoerOpako	2 COATS

TECHNICAL SPECIFICATIONS (for contracts and quotations)

GENERAL CHARACTERISTICS	extra matt water-based paint for interiors
DRY RESIDUE	64.7 ± 0.5% p/p
SPECIFIC WEIGHT	1.60 ± 0.05 g/cm ³ at 20°C



GENERAL INFORMATION AND NOTICES

Store the product in a cool place. Do not allow to freeze.

The technical information provided above is the result of careful laboratory testing and practical experience. Nevertheless, as the product is often used outside our control, we are unable to guarantee the quality of the end result. This information is subject to review by the Company.

Please carefully read the "GENERAL RECOMMENDATIONS".

CQ Rev. 0 - February 2013

"In accordance with European Directive 2004/42/EC, the VOC values displayed on the packaging refer to the dilutions and thinners specified and to tinted products based on the formulations indicated by Boero Bartolomeo SpA."