



# Laser 55

## TDS

COD. 360/....

Anti-mould additive providing protection against the formation of moulds, mosses and algae on interior and exterior walls.

Recommended for areas where damp and condensation are particularly common, including bathrooms, kitchens, cellars, garages, public establishments, etc.

### TYPICAL CHEMICAL AND PHYSICAL CHARACTERISTICS

APPEARANCE	opalescent fluid paste
COMPOSITION	anti-mould additive with active organic substances
SPECIFIC WEIGHT	1.06 ± 0.02 g/cm <sup>3</sup> at 20°C
VISCOSITY	1750 ± 250 cP at 20°C with Brookfield RVT (F4 V50)

For reference standards, see “Key – technical data sheets”

### USAGE

Add the product to your chosen water-based finish. To facilitate mixing, we recommend dispersing LASER 55 in the amount of water needed to dilute the paint.

	DOSAGE
INTERIORS	1 pack (0.25 L) each 13-15 L / 25 kg of product
EXTERIORS	2 packs each 13-15 L / 25 kg of product

### APPLICATION SYSTEM

**SUBSTRATES:** any substrate suitable for re-coating with water-based wall paints, quartz coatings, etc.

**SUBSTRATE PREPARATION:** substrates must be clean, dry and free of moulds, lichens and other micro-organisms. Pre-treat with Laser 23.

### COLOURS

White,





# Laser 55

## TDS

COD. 360/....

### GENERAL INFORMATION AND NOTICES

The addition of Laser 55 to water-based paint does not change drying time, which remains as stated for the product.

Before handling the product, we recommend reading the "SAFETY DATA SHEET".

Shake before use.

Remove all food products from the area.

Store the product in a cool place. Do not allow to freeze.

*The technical information provided above is the result of careful laboratory testing and practical experience. Nevertheless, as the product is often used outside our control, we are unable to guarantee the quality of the end result. This information is subject to review by the Company.*

*Please carefully read the "GENERAL RECOMMENDATIONS".*

**CQ Rev. 4 - March 2010**

***"In accordance with European Directive 2004/42/EC, the VOC values displayed on the packaging refer to the dilutions and thinners specified and to tinted products based on the formulations indicated by Boero Bartolomeo SpA."***